**AMENDMENTS TO THE CLAIMS:** 

Kindly amend claims 2 and 7-9, as shown below.

This listing of claims will replace all prior versions and listings of claims in the

Application:

Claim 1 (cancelled)

Claim 2 (currently amended): A fabrication method [[of]] for fabricating a liquid crystal

display panel by the liquid crystal falling drop method, comprising the steps of:

forming a deformable seal member on at least one of a pair of opposing transparent

substrates such that said seal member surrounds a display area of said liquid crystal display

panel;

arranging first spacers on said display area on said substrate, said first spacers having an

initial size in a cell gap direction larger than an appropriate cell gap necessary to fabricate an

appropriate liquid crystal display;

dropping a volume of liquid crystal onto an area surrounded by said seal member on

one of said transparent substrates;

forming a panel by sticking one of said transparent substrates on the other with said seal

member in a vacuum chamber;

putting said panel under atmospheric pressure to deform said first spacers through a

deformation of said panel due to a difference between said atmosphere pressure and a negative

pressure inside said panel; and

hardening said seal member after an inner volume of said panel becomes equal to [[a]]

the volume of said liquid crystal,

TUCSON, AZ 85718
TEL. 520.882.7623
FAX. 520.882.7643

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE

SUITE 140

175 CANAL STREET
MANCHESTER, NH 03101
TEL. 603.668.1400
FAX. 603.668.8567

2

wherein at least one of said first spacers is elastically deformed from an initial size thereof to a size corresponding to said appropriate cell gap before said seal member is deformed, and

wherein a relative value of an initial average size of said first spacers to said appropriate cell gap is within a range of 102.9% to 107.0%.

Claim 3 (previously presented): A fabrication method of a liquid crystal display panel, as claimed in claim 2, wherein said seal member contains second spacers mixed therein, said second spacers being formed of a material, which is hardly deformed when it is pinched between said transparent substrates under atmospheric pressure.

Claim 4 (previously presented): A fabrication method of a liquid crystal display panel, as claimed in claim 2, wherein said first spacers are deformed to the size corresponding to said appropriate cell gap.

Claim 5 (cancelled)

Claim 6 (previously presented): A fabrication method of a liquid crystal display panel, as claimed in claim 2, wherein the relative value is  $(105 \pm 2)$  %.

Claim 7 (currently amended): A fabrication method [[of]] for fabricating a liquid crystal display panel by the liquid crystal falling drop method, comprising the steps of:

forming a deformable seal member on at least one of a pair of opposing transparent substrates such that said seal member surrounds a display area of said liquid crystal display panel;

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643

arranging first spacers on said display area on said substrate, said first spacers having an initial size in a cell gap direction larger than an appropriate cell gap necessary to fabricate an appropriate liquid crystal display;

dropping <u>a volume</u> liquid crystal onto an area surrounded by said seal member on one of said transparent substrates;

forming a panel by sticking one of said transparent substrates on the other with said seal member in a vacuum chamber;

putting said panel under atmospheric pressure to deform said first spacers through a deformation of said panel without hardening said seal member, wherein excessive deformation of said panel due to atmospheric pressure is prevented by compressive stress of spacers located at a central region of said panel; and

hardening said seal member after an inner volume of said panel becomes equal to [[a]] the volume of said liquid crystal,

wherein at least one of said first spacers are elastically deformed from an initial size thereof to a size corresponding to said appropriate cell gap before said seal member is deformed and said seal member contains second spacers mixed therein, said second spacers being formed of a material, which is hardly deformed when it is pinched between said transparent substrates under atmospheric pressure, and

wherein a relative value of an initial average size of said first spacers to said appropriate cell gap is within a range of 102.9% to 107.0%.

Claim 8 (currently amended): A fabrication method [[of]] for fabricating a liquid crystal display panel by the liquid crystal falling drop method, comprising the steps of:

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643

forming a deformable seal member on at least one of a pair of opposing transparent substrates such that said seal member surrounds a display area of said liquid crystal display panel;

arranging first spacers on said display area on said substrate, said first spacer having an initial size in a cell gap direction larger than an appropriate cell gap necessary to fabricate an appropriate liquid crystal display;

dropping <u>a volume</u> liquid crystal onto an area surrounded by said seal member on one of said transparent substrates;

forming a panel by sticking one of said transparent substrates on the other with said seal member in a vacuum chamber;

putting said panel under atmospheric pressure to deform said first spacers through a deformation of said panel without hardening said seal member, wherein excessive deformation of said panel due to atmospheric pressure is prevented by compressive stress of spacers located at a central region of said panel; and

hardening said seal member after an inner volume of said panel becomes equal to [[a]]

the volume of said liquid crystal,

wherein at least one of said first spacers is elastically deformed from an initial size thereof to a size corresponding to said appropriate cell gap before said seal member is deformed and said first spacer is deformed to the size corresponding to said appropriate cell gap, and

wherein a relative value of an initial average size of said first spacers to said appropriate cell gap is within a range of 102.9% to 107.0%.

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643

Claim 9 (currently amended): A fabrication method [[of]] for fabricating a liquid crystal display panel by the liquid crystal falling drop method, comprising the steps of:

forming a deformable seal member on at least one of a pair of opposing transparent substrates such that said seal member surrounds a display area of said liquid crystal display panel;

arranging first spacers on said display area on said substrate, said first spacer having an initial size in a cell gap direction larger than an appropriate cell gap necessary to fabricate an appropriate liquid crystal display;

dropping <u>a volume</u> liquid crystal onto an area surrounded by said seal member on one of said transparent substrates;

forming a panel by sticking one of said transparent substrates on the other with said seal member in a vacuum chamber without hardening said seal member;

putting said panel under atmospheric pressure to deform said first spacers together with said liquid crystal through a deformation of said panel such that said deformation of said panel proceeds in a center portion of said panel at higher speed than that in a peripheral portion thereof due to a difference between atmospheric pressure and a negative pressure inside said panel, wherein said first spacers located at a central portion of said panel is deformed firstly together with said liquid crystal to provide an appropriate cell gap prior to said seal member being deformed; and

hardening said seal member after an inner volume of said panel becomes equal to [[a]]

the volume of said liquid crystal, and

wherein a relative value of an initial average size of said first spacers to said appropriate cell gap is within a range of 102.9% to 107.0%.

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643